

EU00040

ENEOS Premium 10W40

Synthetic Motor Oil

ENEOS Premium 10W40 is synthetic engine oil recommended for gasoline and diesel engines. Because of the high viscosity index and the synthetic base stocks, the oil assures an excellent cold start with outstanding lubricating film at high temperatures. **ENEOS Premium 10W40** takes care of trouble free functioning of the engine, because of the chosen additive package. In addition, together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

● SPECIAL FEATURES

1. Synthetic Motor Oil

ENEOS Premium 10W40 is blended from synthetic base oils and optimized additives, so its high-temperature oxidation stability is superior to motor oils made from mineral base oils.

2. Reducing Fuel consumption

ENEOS Premium 10W40 helps reducing the fuel consumption as well as reducing emission levels. Because of the unique formulation a low evaporation under severe operating conditions is guaranteed.

3. Excellent Resistance for Wear, Corrosion, Foaming and Oxidation

ENEOS Premium 10W40 gives optimum protection against wear and has strong anti-corrosion and anti-foam characteristics as well as high resistance against oxidation.

● PERFORMANCE LEVEL

API SL/CF, ACEA: A3/B3/B4

VW 500.00/505.00, MB 229.1, Porsche, BMW Special Oil

● APPLICATION

Motor oil for gasoline and diesel engines of Cars and Commercial vehicles including Mini Buses & Trucks

● CONTAINERS

1L, 4L, 20L, 200L, 1000L IBC

● Typical Properties

SAE viscosity grade	10W-40
Density (20°C), g/cm ³	0.869
Flash point (COC), °C	210
Kinematic viscosity (40°C), mm ² /s	99.6
(100°C), mm ² /s	14.7
Viscosity index	154
Pour point, °C	-33.0

Note: The typical properties may be changed without notice. (February 2006)