

EU00050

ENEOS Super Plus 15W40

Motor Oil

ENEOS Super Plus 15W40 is developed according the latest oil and exhaust emissions requirements, for viscosity increase and wear. It has an excellent cleaning ability. **ENEOS Super Plus 15W40** is especially suitable for mixed fleet applications, like gasoline, LPG and light diesel engines, with or without turbo and/or catalytic converter. In addition, **ENEOS Super Plus 15W40** fulfills the latest, strict norms concerning deposits on the piston crown, the upper piston-ring groove and the rest of the pistons and exceeds the demands of manufacturers in the automotive sector.

● SPECIAL FEATURES

1. Reduced Oil Stock Level

ENEOS Super Plus 15W40 is a universal oil blended with carefully selected base oils and additives for the broad applications in gasoline, LPG and light diesel engines. This gives benefit to reduce the oil stock space considerably at the wholesaler or fleet-owner.

2. Excellent Resistance for Wear, Corrosion, Foaming and Oxidation

ENEOS Super Plus 15W40 gives optimum protection against wear and has anti-corrosion and anti-foam characteristics as well as a high resistance against oxidation.

● PERFORMANCE LEVEL

API: CG-4/CF-4/CF/SJ, ACEA: A2/B3/E2/A3

VW 501/505, MB: 228.1, 229.1, Volvo: VDS, MAN: 271, Mack: EO/L

● APPLICATION

Motor oil for mixed fleet applications, like gasoline, LPG and light diesel engines, with or without turbo and/or catalytic converter.

● CONTAINERS

1L, 4L, 18L, 200L, 1000 IBC

● Typical Properties of

SAE viscosity grade	15W-40
Density (20°C), g/cm ³	0.879
Flash point (COC), °C	215
Kinematic viscosity (40°C), mm ² /s	102.5
(100°C), mm ² /s	13.9
Viscosity index	137
Pour point, °C	-27.0

Note: The typical properties may be changed without notice. (February 2006)