

EU00070

ENEOS Premium Multi Gear 75W90

Gear Oil (Manual Transmission Oil)

ENEOS Premium Multi Gear 75W90 is ENEOS Premium Multi Gear is synthetic, universal transmission/gear oil which can be applied in both manual gearboxes as well as in final drives, where API GL-5 quality oil is prescribed.

ENEOS Premium Multi Gear can be used for the Complete drive line. The product contains special additives reducing fuel consumption and eliminating shifting problems. Due to this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures the oil is protected against thermal oxidation.

● SPECIAL FEATURES

1. Superior Extreme Pressure Performance

This Oil shows excellent EP (Extreme Pressure) characteristics providing an adequate protection even under high shock loads and vibrations.

2. Excellent Resistance for Wear, Corrosion, Foaming and Oxidation

This Oil shows an excellent resistance against wear, corrosion and foaming as well as oxidation and ageing at elevated temperatures.

● PERFORMANCE LEVEL

API GL-5

MIL-L-2105-D

Mack GO-G

ZF TE-ML 05A,12A

MAN 342 N / MAN 342 type M-1

● APPLICATION

Recommended for use in manual gearboxes (synchronised or non-synchronised) as well as in final drives, where an API GL-5 quality oil is prescribed

● CONTAINERS

1L, 4L, 20L, 200L, 1000L IBC

● TYPICAL PROPERTIES

SAE viscosity grade	75W-90
Density (20°C), g/cm ³	0.8834
Flash point (COC), °C	204
Kinematic viscosity (40°C), mm ² /s	79.9
(100°C), mm ² /s	14.6
Viscosity index	192
Pour point, °C	-42.0

Note: The typical properties may be changed without notice.
(February 2006)